

Description:

Zaitak 10W is high Performance mono-grade Diesel Engine Oil **Zaitak 10W** is recommended for use in naturally-aspirated, turbo-charged and super-charged diesel engines that operate at diverse conditions.

Benefits :

- It could be used in some certain hydraulic and transmission systems.
- Maintains cleanliness of the engine due to its high content detergents and dispersants.
- High Level of protection against oxidation, wear and corrosion are also guaranteed.
- Made from 100% virgin base oil.

Performance Levels:

- API CF/SF
- MB 228.0
- MAN 270

Specifications:

Zaitak 10W



#	Test	Unit	Method	Control Limit	Typical Test Result
1	Viscosity Grade	-	-	SAE 10W	SAE 10W
2	Kinematic Viscosity @ 100°C	cSt	ASTM D445	4.10 (min)	5.90
3	Viscosity Index	-	ASTM D2270	95 (min)	105
4	Flash Point	°C	ASTM D92	205 (min)	226
5	Pour Point	°C	ASTM D97	-33 (max)	-33
6	Total Base Number	mgKOH/g	ASTM D2896	8.0 (min)	10.0
7	Foaming Seq I	ml/ml	ASTM D892	25/0 (max)	0/0
8	Foaming Seq II	ml/ml	ASTM D892	50/0 (max)	0/0
9	Foaming Seq III	ml/ml	ASTM D892	25/0 (max)	0/0
10	Dynamic Viscosity @-25°C	cP	ASTM D-5293	7000 (max)	4400

Member of Sayegh Group