

**Description:**

**Zaitak 40** is high Performance mono-grade Diesel Engine Oil **Zaitak 40** is recommended for use in naturally-aspirated, turbo-charged and super-charged diesel engines that operate at diverse conditions.

**Benefits :**

- Maintains cleanliness of the engine due to its high content detergents and dispersants.
- High Level of protection against oxidation, wear and corrosion are also guaranteed.
- Made from 100% virgin base oil.

**Performance Levels:**

- API CF/SF
- MB 228.0
- MAN 270

**Specifications:**

**Zaitak 40**



#	Test	Unit	Method	Control Limit	Typical Test Result
1	Viscosity Grade	-	-	SAE 40	SAE 40
2	Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.50 – 16.30	14.6
3	Viscosity Index	-	ASTM D2270	95 (min)	96
4	Flash Point	°C	ASTM D92	230 (min)	246
5	Pour Point	°C	ASTM D97	-15 (max)	-15
6	Total Base Number	mgKOH/g	ASTM D2896	8.0 (min)	10.0
7	Foaming Seq I	ml/ml	ASTM D892	25/0 (max)	0/0
8	Foaming Seq II	ml/ml	ASTM D892	50/0 (max)	0/0
9	Foaming Seq III	ml/ml	ASTM D892	25/0 (max)	0/0

Member of Sayegh Group