

Description:

Zaitak Automatic Transmission Fluid (III) is typically used in passenger-car automatic transmissions, power steering units and hydraulic power systems. **Zaitak ATF-III** contains special additives: antioxidants, antifoam agents, viscosity modifiers, antiwear additives, friction modifiers, detergents, dispersants, corrosion inhibitors and seal swell agents. It is traditionally dyed red to distinguish it from engine oils.

Benefits :

- Used for all applications that require Dexron, Dexron II and Dexron III fills.
- It is resistant to oil degradation, highly shear stable with good properties against friction and dependable anti-wear protection.
- Made from 100% virgin base oil.

Performance Levels:

- D- III G
- Ford M
- Allison C-4
- MB –Approval 236.9
- Voith 55.6335 .xx (G607)

**Specifications:****Zaitak Automatic Transmission Fluid III:**

<u>Test</u>	<u>Unit</u>	<u>Method</u>	<u>Control Limit</u>	<u>Typical Test Result</u>
Appearance	-	-	-	B & C
Kinematic Viscosity @ 100°C	cSt	ASTM D445	6.5 – 9.0	7.8
Viscosity Index	-	ASTM D2270	160 (min)	185
Flash Point	°C	ASTM D92	170 (min)	200
Pour Point	°C	ASTM D97	-	-45
Foaming Seq I	ml/ml	ASTM D892	50/0 (max)	0/0
Foaming Seq II	ml/ml	ASTM D892	50/0 (max)	0/0
Foaming Seq III	ml/ml	ASTM D892	50/0 (max)	0/0
Brookfield Viscosity @ -20°C	cP	ASTM D2983	1500 (max)	1400
Brookfield Viscosity @ -40°C	cP	ASTM D2983	20000 (max)	16400

Member of Sayegh Group