

Product Data Sheet

Zaitak Compressor Oil

Jordan National Lube Oil Co.
الشركة الوطنية الأردنية لصناعة الزيوت المعدنية

Description:

Zaitak Compressor Oil is a premium quality compressor lubricant which is blended with highly refined paraffinic base oils and an ashless additive package with an outstanding oxidation and corrosion inhibiting properties.

Benefits :

- High oxidation stability.
- Good thermal stability.
- Excellent hydrolytic stability.
- No sludge formation.
- Very low acid number.
- Good protection against corrosion of steel and non-ferrous metals.
- Good demulsifying behavior.
- Good foam behavior.
- Made from 100% virgin base oil.

Performance Levels:

- DIN 51506 (VBL, VCL, VDL)
- ISO DP/6521 (DAA, DAB, DAH, DAG).



Specifications:

Zaitak Compressor Oil ISO 46:

#	Test	Unit	Method	Typical Test Result
1	Viscosity Grade	-	-	ISO 46
2	Kinematic Viscosity @ 100°C	cSt	ASTM D445	7.2
3	Kinematic Viscosity @ 40°C	cSt	ASTM D445	46
4	Viscosity Index	-	ASTM D2270	102
5	Flash Point	°C	ASTM D92	228
6	Pour Point	°C	ASTM D97	-30
7	Foaming Seq I	ml/ml	ASTM D892	5/0
8	Foaming Seq II	ml/ml	ASTM D892	10/0
9	Foaming Seq III	ml/ml	ASTM D892	5/0

Member of Sayegh Group

Tel: (962-6) 4794455 Fax: (962-6) 4740071 P.O.Box : 566 Abu-Alanda 11592 Jordan
Info@zaitak.com www.sayeghgroup.com

Product Data Sheet
Zaitak Compressor Oil

Jordan National Lube Oil Co.
الشركة الوطنية الأردنية لصناعة الزيوت المعدنية

Zaitak Compressor Oil ISO 68:

<u>#</u>	<u>Test</u>	<u>Unit</u>	<u>Method</u>	<u>Typical Test Result</u>
1	Viscosity Grade	-	-	ISO 68
2	Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.01
3	Kinematic Viscosity @ 40°C	cSt	ASTM D445	70.6
4	Viscosity Index	-	ASTM D2270	101
5	Flash Point	°C	ASTM D92	248
6	Pour Point	°C	ASTM D97	-30
7	Foaming Seq I	ml/ml	ASTM D892	5/0
8	Foaming Seq II	ml/ml	ASTM D892	10/0
9	Foaming Seq III	ml/ml	ASTM D892	5/0



Member of Sayegh Group

Tel: (962-6) 4794455 Fax: (962-6) 4740071 P.O.Box : 566 Abu-Alanda 11592 Jordan
Info@zaitak.com www.sayeghgroup.com