

## Product Data Sheet

### Zaitak Gold SAE 10W-40

Jordan National Lube Oil Co.  
الشركة الوطنية الأردنية لصناعة الزيوت المعدنية

#### Description:

**Zaitak Gold SAE 10W-40** is high Performance multi-grade Gasoline Engine Oil **Zaitak Gold SAE 10W-40** is recommended for use in all modern vehicles including high performance turbo-charged, with multi-valve direct injection gasoline and diesel engines of all modern European, American, Japanese and Korean vehicles.

#### Benefits :

- Enriched with new-technology chemical additives that maintains minimum sludge and deposits at elevated temperatures.
- A multi-grade lubricant that prolongs engine's lifetime and also ease of startup at extremely low and high temperatures since it ensures 'stay in viscosity matrix' for extended period of time.
- Made from 100% virgin base oil.

#### Performance Levels:

- API SL/CF
- MB 229.1
- ACEA A3, B3-12
- ACEA A3, B4-12



#### Specifications:

##### **Zaitak Gold SAE 10W-40**

#	Test	Unit	Method	Control Limit	Typical Test Result
1	Viscosity Grade	-	-	SAE 10W-40	SAE 10W-40
2	Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.50-16.30	14.30
3	Viscosity Index	-	ASTM D2270	95 (min)	125
4	Flash Point	°C	ASTM D92	205 (min)	215
5	Pour Point	°C	ASTM D97	-33 (max)	-33
6	Total Base Number	mgKOH/g	ASTM D2896	6.0 (min)	9.0
7	Foaming Seq I	ml/ml	ASTM D892	25/0 (max)	0/0
8	Foaming Seq II	ml/ml	ASTM D892	50/0 (max)	0/0
9	Foaming Seq III	ml/ml	ASTM D892	25/0 (max)	0/0
10	Dynamic Viscosity @-25°C	cP	ASTM D-5293	7000 (max)	6200

Member of Sayegh Group

Tel: (962-6) 4794455 Fax: (962-6) 4740071 P.O.Box : 566 Abu-Alanda 11592 Jordan  
Info@zaitak.com www.sayeghgroup.com