Product Data Sheet Zaitak Industrial Gear Oil

Jordan National Lube Oil Co.

الشركة الوطنية الأردنية لصناعة الزيوت المعدنية

Description:

Zaitak Industrial Gear Oil is a premium-quality, lead-free oil designed for use in extreme-pressure heavyduty industrial gears. It guarantees top performance in gears and in other industrial applications due to the combination of its high-load carrying capacity and anti-friction characteristics.

Benefits:

- Unique sulfur-phosphorus technology that results in low-odor gear oils.
- This lubricant contains newly formulated additives that add excellent load carrying capacity, anti-friction characteristics, outstanding thermal and oxidation stability, reliable corrosion prevention. It also reduces the risk of premature gear failures due to micro-pitting.
- To be used with steel gear transmissions, industrial gear drives where full EP performance is required, bearings and in circulating and splash lubricated systems.

Zaitak

Made from 100% virgin base oil.

Performance Levels:

- AGMA 252.04
- ISO 12925-1 CKC
- ISO 6743 -6 CKC
- US Steel 224 •
- DIN 51517 Part III

Specifications:

Zaitak Industrial Gear Oil

<u>#</u>	Test	<u>Unit</u>	Method	<u>ISO</u> <u>68</u>	<u>ISO</u> <u>100</u>	<u>ISO</u> <u>150</u>	<u>ISO</u> 220	<u>ISO</u> <u>320</u>	<u>ISO</u> <u>460</u>
1	Kinematic Viscosity @ 100°C	cSt	ASTM D445	-	-	-	-	-	-
2	Kinematic Viscosity @ 40°C	cSt	ASTM D445	68	100	150	220	320	460
3	Viscosity Index, min	-	ASTM D2270	90	90	90	90	90	90
4	Flash Point, min	°C	ASTM D92	180	200	200	200	200	200
5	Pour Point, max	°C	ASTM D97	-15	-12	-9	-9	-6	-6
6	Copper Strip corrosion, 100C 3hr, max	-	ASTM D130	1	1	1	1	1	1
7	Foaming Seq I, max	ml/ml	ASTM D892	10/100	10/100	10/100	10/100	10/100	10/100
8	Foaming Seq II,max	ml/ml	ASTM D892	10/100	10/100	10/100	10/100	10/100	10/100
9	Foaming Seq III,max	ml/ml	ASTM D892	10/100	10/100	10/100	10/100	10/100	10/100

Member of Sayegh Group

Tel: (962-6) 4794455 Fax: (962-6) 4740071 P.O.Box : 566 Abu-Alanda 11592 Jordan Info@zaitak.com www.sayeghgroup.com