

**Description:**

**Zaitak Power** is high Performance multi-grade Diesel Engine Oil **Zaitak Power** is a modern premium quality diesel engine lubricant that is recommended for use in naturally-aspirated, turbo-charged and super-charged diesel engines operating at diverse conditions.

**Benefits :**

- Suitable for all American, European, Japanese and Korean vehicles.
- Its high TBN content maintains internal cleanliness of the engine and minimizes ash deposits, which prolongs the operating lifetime of the engine. Therefore, it is suitable for engines running at high-sulfur containing fuels.
- Blended with premium and highly shear-stable viscosity index improver along with high-performance chemical additives which renders it a multi-grade lubricant to withstand toughest operating conditions, easier startup, thermal stability, minimum engine wear and minimum oil loss.
- Made from 100% virgin base oil.

**Performance Levels:**

- API CI-4/SL
- Volvo VDS-3
- MB 228.3
- Mack EO-M Plus
- MAN 3275
- MTU Type 2
- ACEA E7-08
- Cummins CES 20078
- ACEA A3, B4-08
- Detroit Diesel 93K215
- Caterpillar ECF-2
- JASO DH-1



**Specifications:**

**Zaitak Power**

#	Test	Unit	Method	Control Limit	Typical Test Result
1	Viscosity Grade	-	-	SAE 15W40	SAE 15W40
2	Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.50 – 16.30	14.3
3	Viscosity Index	-	ASTM D2270	95 (min)	130
4	Flash Point	°C	ASTM D92	210 (min)	220
5	Pour Point	°C	ASTM D97	-27 (max)	-27
6	Total Base Number	mgKOH/g	ASTM D2896	8.0 (min)	16.0
7	Foaming Seq I	ml/ml	ASTM D892	25/0 (max)	0/0
8	Foaming Seq II	ml/ml	ASTM D892	50/0 (max)	0/0
9	Foaming Seq III	ml/ml	ASTM D892	25/0 (max)	0/0
10	Dynamic Viscosity @ -20°C	cP	ASTM D-5293	7000 (max)	6000

Member of Sayegh Group